California Department of Public Health Compliance Form

Anti-Entrapment Devices and Systems for Public Pools and Spas

County of San Diego Department of Environmental Health Food and Housing Division (858) 505-6659
Permit # FR
Plan Check #
Date

Use one form for <u>each pump</u> or <u>multiple pumps under the same drain cover</u>
ALL SECTIONS OF THIS FORM MUST BE COMPLETED.

This form is to be used to verify compliance with modifications pursuant to the new Health and Safety Code sections 116064.1 and 116064.2. Under Section 116064.2 (a) of the Health and Safety Code, effective January 1, 2010, the owner of a public swimming pool shall file this form within 30 days following the completion of construction or installation of antientrapment devices or systems in swimming pools. Contact your local Environmental Health Department and Building Department for any necessary plan approval and permits prior to construction or remodel.

Site Information				
Facility Name:		Pool Identification (if more than 1 pool/spa at site):		
Facility Address:		City:	St:Zip:	
Owner Name:		Owner's Phone #:		
Owners Address:		City:	St:Zip:	
Was pool constructed on/ after				
Pump Information				
□ Recirculation Pump		 Jet / Booster Pump 		
Make/Model	H.P.	Make/Model	H.P	
□ Other Pump:		□ Feature Pump		
Other Pump:Make/Model	H.P	Make/Model	H.P	
Main Drain (includes all suct	ion outlets except Skim	mer Equalizer Lines)		
Manufacturer of approved drain	n cover:	Model Number:	Install date:	
		Installed on 🛛 Floor 🔻 Wall		
Manufacturer of approved drain	n cover:	Model Number:	Install date:	
		Installed on = Floor = Well Main d	Irain/ let suction nine size is inches	
GPM rating: Floor Check One: Split main drain(s) (Minimu Single drain – Unblockable Single drain – Not unblockasystem, gravity drainage sy	im 3 ft. between covers, he (size and shape that a he able (one of the following ystem, auto pump shut-off	nydraulically balanced and symmetrically plu uman body cannot sufficiently block to crea secondary devices is required: safety vacu f system, or other equally or more effective	umbed) ate a suction entrapment) ate a suction entrapment) ate a suction entrapment suction limiting vent system approved by enforcement agency)	
GPM rating: Floor Check One: Split main drain(s) (Minimu Single drain – Unblockable Single drain – Not unblockable system, gravity drainage sy Type of secondary device in Manufacturer of approved	im 3 ft. between covers, he (size and shape that a he able (one of the following ystem, auto pump shut-offinstalled:	nydraulically balanced and symmetrically plo uman body cannot sufficiently block to crea secondary devices is required: safety vacu	umbed) ate a suction entrapment) num release system, suction limiting vent system approved by enforcement agency)Install date: /Part Number:	
GPM rating: Floor Check One: Split main drain(s) (Minimu Single drain – Unblockable Single drain – Not unblocka system, gravity drainage sy Type of secondary device i Manufacturer of approved Safety vacuum release sys	im 3 ft. between covers, he (size and shape that a he able (one of the following ystem, auto pump shut-offinstalled:	nydraulically balanced and symmetrically plo uman body cannot sufficiently block to crea secondary devices is required: safety vacu f system, or other equally or more effective	umbed) ate a suction entrapment) num release system, suction limiting vent system approved by enforcement agency)Install date: /Part Number:	
GPM rating: Floor Check One: Split main drain(s) (Minimu Single drain – Unblockable Single drain – Not unblock system, gravity drainage sy Type of secondary device i Manufacturer of approved Safety vacuum release sys	im 3 ft. between covers, he (size and shape that a heable (one of the following ystem, auto pump shut-offinstalled:	nydraulically balanced and symmetrically plo uman body cannot sufficiently block to crea secondary devices is required: safety vacu f system, or other equally or more effective	umbed) ate a suction entrapment) aum release system, suction limiting vent system approved by enforcement agency)Install date:/Part Number: F2387 □ ASME/ANSI standard A112.19.1	
GPM rating: Floor Check One: Split main drain(s) (Minimu Single drain – Unblockable Single drain – Not unblock system, gravity drainage sy Type of secondary device Manufacturer of approved Safety vacuum release sys	im 3 ft. between covers, he (size and shape that a he able (one of the following ystem, auto pump shut-off installed:device:stem bears the following pation fitting:	nydraulically balanced and symmetrically pluman body cannot sufficiently block to creat secondary devices is required: safety vacuif system, or other equally or more effective Model. Derformance standard markings: Model Number:	umbed) ate a suction entrapment) aum release system, suction limiting vent system approved by enforcement agency)Install date:/Part Number: F2387 □ ASME/ANSI standard A112.19.1	
GPM rating: Floor Check One: Split main drain(s) (Minimu Single drain – Unblockable Single drain – Not unblockable system, gravity drainage sy Type of secondary device i Manufacturer of approved Safety vacuum release sys Skimmer Equalizer Line(s) Manufacturer of approved suct GPM rating: GPM rating: Floor	am 3 ft. between covers, he (size and shape that a he able (one of the following ystem, auto pump shut-off installed:	nydraulically balanced and symmetrically pluman body cannot sufficiently block to creat secondary devices is required: safety vacuif system, or other equally or more effective Model. Derformance standard markings: Model Number:	umbed) ate a suction entrapment) aum release system, suction limiting vent system approved by enforcement agency)Install date: /Part Number: F2387	
GPM rating: Floor Check One: Split main drain(s) (Minimu	im 3 ft. between covers, he (size and shape that a he able (one of the following ystem, auto pump shut-off installed:device:stem bears the following particle fitting: Wall_size were found to be	nydraulically balanced and symmetrically pluman body cannot sufficiently block to crea secondary devices is required: safety vacu f system, or other equally or more effective Model. Model Number: Installed on □ Flo	umbed) ate a suction entrapment) aum release system, suction limiting vent system approved by enforcement agency)Install date: /Part Number: F2387 □ ASME/ANSI standard A112.19.1Install date ers:	
GPM rating: Floor Check One: Split main drain(s) (Minimu	am 3 ft. between covers, he (size and shape that a he able (one of the following ystem, auto pump shut-off installed:	nydraulically balanced and symmetrically pluman body cannot sufficiently block to creat secondary devices is required: safety vacuif system, or other equally or more effective Model. Model Number: Installed on □ Floom inches Number of Skimm	umbed) ate a suction entrapment) aum release system, suction limiting vent system approved by enforcement agency)Install date: /Part Number: F2387	
GPM rating: Floor Check One: Split main drain(s) (Minimu	am 3 ft. between covers, he (size and shape that a he able (one of the following ystem, auto pump shut-offinstalled: device: stem bears the following particles were found to be D VERIFIED TO COMPLY of California State Contracted #w best of my knowledge. I stion of the licensing authors	nydraulically balanced and symmetrically pluman body cannot sufficiently block to crea secondary devices is required: safety vacuated from the system, or other equally or more effective more feromence standard markings: Model Number: Installed on Flow inches	umbed) ate a suction entrapment) aum release system, suction limiting vent system approved by enforcement agency)	
Check One: Split main drain(s) (Minimu Single drain – Unblockable Single drain – Not unblockable Single drain – Not unblockable system, gravity drainage sy Type of secondary device in Manufacturer of approved Safety vacuum release system Skimmer Equalizer Line(s) Manufacturer of approved suctable GPM rating: GPM rating: Floor Skimmer equalizer line(s) pipe THE ABOVE HAS BEEN FIELD I declare that I hold an active Professional Engineer license provided above is true to the disciplinary action at the discree Contractor/Engineer Name:	am 3 ft. between covers, he (size and shape that a he able (one of the following ystem, auto pump shut-off installed:	nydraulically balanced and symmetrically pluman body cannot sufficiently block to creat secondary devices is required: safety vacuif system, or other equally or more effective Model, performance standard markings: Model Number: Installed on Installed on Flow Flow Inches Number of Skimm MITH MANUFACTURER'S INSTALLATION or license # with class with qualified experience working on public understand that if I improperly certify this ority in accordance with California Health & Company Name:	umbed) ate a suction entrapment) aum release system, suction limiting vent system approved by enforcement agency)Install date: /Part Number: F2387	
GPM rating: Floor Check One: Split main drain(s) (Minimu	am 3 ft. between covers, he (size and shape that a he able (one of the following ystem, auto pump shut-off installed:	nydraulically balanced and symmetrically pluman body cannot sufficiently block to creat secondary devices is required: safety vacuated from the system, or other equally or more effective model. Model	umbed) ate a suction entrapment) aum release system, suction limiting vent system approved by enforcement agency)	
GPM rating: Floor Check One: Split main drain(s) (Minimu Single drain – Unblockable Single drain – Not unblock system, gravity drainage sy Type of secondary device i Manufacturer of approved Safety vacuum release system Skimmer Equalizer Line(s) Manufacturer of approved suct GPM rating: GPM rating: Floor Skimmer equalizer line(s) pipe THE ABOVE HAS BEEN FIELE I declare that I hold an active Professional Engineer license provided above is true to the disciplinary action at the discret Contractor/Engineer Name: Company Address:	am 3 ft. between covers, he (size and shape that a he able (one of the following ystem, auto pump shut-off installed: device: stem bears the following particles and fitting: Wall size were found to be O VERIFIED TO COMPLY California State Contracted #w best of my knowledge. I	nydraulically balanced and symmetrically pluman body cannot sufficiently block to crea secondary devices is required: safety vacuated from the system, or other equally or more effective more feromenance standard markings: Model Number: Installed on Flow inches Number of Skimmed Skimme	umbed) ate a suction entrapment) aum release system, suction limiting vent system approved by enforcement agency)Install date: /Part Number: F2387	

California Department of Public Health Compliance Form Anti-Entrapment Devices and Systems for Public Pools and Spas

Health & Safety Code Sections 116064.1 and 116064.2

INSTRUCTIONS FOR COMPLETING THE COMPLIANCE FORM

- Use one form for each pump or multiple pumps under the same drain cover. For example, a spa with a recirculation
 pump and a jet pump each with their own set of split drains that terminate under a different drain cover will require
 two forms. However, two pumps with split drains that terminate under the same drain cover will require only one
 form.
- All sections of the form must be completed. An incomplete form will invalidate certification.
- · Print legibly.
- Return the completed form to your local Environmental Health Department.

I. Site Information

- A. Facility name name of facility or DBA (e.g. Oak Glen HOA, Palms Apartments).
- B. Pool Identification description of the pool which will identify it when there is more than one pool on the property.
- C. Facility Address address, city, state, and zip code of the facility where the pool or pools are located.
- D. Owner's name owner, owner's representative, or corporation name.
- E. Owner's address address, city, state, zip, and telephone number of the owner or owner's representative.
- F. Indicate if the pool was constructed on or after January 1, 2010.

II. Pump Information

A. Identify the type of pump that is connected to the drain. If two pumps terminate under one set of split drains (e.g. one side of a split suction drain is used for both a recirculation pump and a jet pump), describe both pumps. For each pump, provide the make, model number, and horsepower. Remember to complete a separate compliance form if the additional pump is connected to a different drain cover.

III. Main Drain (Includes all suction outlets except skimmer equalizer lines)

- A. Provide the manufacturer, make and model, and the date the drain cover was installed.
- B. Provide the floor and wall flow rating in gallons per minute for the drain cover. Note: If there are two different drain covers (e.g. one on the wall and one on the floor), there is space on the compliance form to complete drain cover information for each drain.
- C. Indicate the size of the pipe terminating at the main drain or jet suction.
- D. Check a box to indicate the configuration of the drain.
 - 1. **Split Main Drains** means there are two drains that are hydraulically balanced and symmetrically plumbed and are separated by a distance of at least three feet in any dimension between the suction outlets.
 - 2. **Single Drain Unblockable** means there is one drain approved to be unblockable so that a human body cannot sufficiently block it to create a suction hazard.
 - 3. **Single Drain Not Unblockable** means there is a single drain which can be sufficiently blocked by a human body to create a suction hazard. This type of drain must be protected by an approved safety vacuum release system or other equally or more effective system. Provide the type of device installed, manufacturer, model, and indicate which type of performance standard is marked on the device (ASTM F2387 or ASME/ANSI standard A112.19.17).

IV. Skimmer Equalizer Line(s)

- A. Provide the manufacturer; make and model; and the date the drain cover was installed.
- B. Provide the floor and wall flow rating in gallons per minute for the drain cover. Note: If there are two different drain covers (e.g. one on the wall and one on the floor), there is space on the compliance form to complete drain cover information for each drain.
- C. Indicate the size of the skimmer equalizer line pipe.
- D. Indicate number of skimmers.

V. Contractor/Engineer Certification Section

- A. Enter the valid California State Contractor's license number.
- B. Enter the Contractor's license classification.
- C. Or enter the California State Professional Engineer's license number, if applicable.
- D. Enter the Contractor's / Engineer's name and the company they are working for.
- E. Enter the company address, city, state, zip code, telephone number, cell phone number, FAX number, and email for the Contractor / Engineer.
- F. Print the name of the Contractor/Engineer.
- G. The Contractor or Engineer must sign the form.
- H. Enter the date the form was signed.

VI. County of San Diego Section

- A. Enter the County of San Diego, Department of Environmental Health Permit # and Plan Check # (if applicable) for the facility and enter the date. The permit # is 6 digits (for example FR00-123456) and the plan check # is 5 digits.
- B. Contact the County of San Diego at (858) 505-6659 with guestions.
- C. Return the completed form to:

Department of Environmental Health, Food & Housing Division, Attn: Operations Supervisor PO Box 129261, San Diego, CA 92112-9261